

LINEAR

HIGH BAY

The naturaLED® Linear High Bay is an excellent option for generating bright, even illumination up to 42,440 lumens. It is designed with common sense features to create a durable and robust fixture.

Manufactured with a 5" wide channel to allow room for accessories like motion sensors or emergency drivers, this DLC Premium fixture has a built-in level for ease of installation.

- 4000K, 5000K
- Up to 42,440 Lumens
- 100, 150, 210 or 300W
- Voltage: 120-277V / 120-347V / 277-480V
- Accessories: Emergency Driver, Motion Sensor, Wireless Controller, Yoke Mount, Pendant Mount, Wireguard

Occupancy & Daylighting, Wireless Programmers and Sensors



Wall Switch/

Bluetooth Controller

Motion & Photocell Sensor/ Remote Programmer















manufactures high performance LED lighting solutions that can reduce energy and lower maintenance costs. Warehouses require lighting to ensure that employees can stay safe and work more efficiently.







naturaLED®



The compact and lightweight Round High Bay is IP66 rated. Engineered with an adjustable pre-installed hook, it can replace traditional 1000-watt HIDs. This versatile fixture comes with several optional accessories; a 120° lens, polycarbonate refractor, and a motion sensor that can be operated with a remote control.

- 5000K
- 100, 150, or 200W
- Up to 32,985 Lumens
- Voltage: 120-277V, 277-480V
- Accessories: Refractor, Lens, Motion Sensor, Remote Control, Pendant Mount























Polycarbonate Refractor/ Lens

Sensor/Remote Controller


Wall Switch/ Bluetooth Controller





COMMERCIAL STRIP / RETROFIT STRIP

- **3CCT 3500K, 4000K, 5000K**
- **22 to 68W**
- Up to 9,398 Lumens
- Dimmable: 0-10V
- Accessories: Motion Sensor, Emergency Driver







The new selectable color and selectable wattage Vapor Tight is just one of several linear lighting options from naturaLED®. Available in 2, 4 or 8 ft. options, this fixture produces up to 13,000 lumens.

Wall / Ceiling Mounting

VAPORTIGHT





- 3CCT 3500K, 4000K, 5000K (except for 8 ft.)
- 20 to 100W
- Up to 13,000 Lumens
- Dimmable: 0-10V
- Accessories: Wall Mount, Motion Sensor, **Emergency Driver**



COMMERCIAL WRAP

- 3CCT 3500K, 4000K, 5000K
- 22/28/34/44W
- Up to 5,720 Lumens
- Dimmable: 0-10V
- Accessories: Emergency Driver, **Motion Sensor**

UTILITY WRAP

- 4000K or 5000K
- 27W
- Up to 3,510 Lumens
- Dimmable: 0-10V Accessories: Emergency Driver, Motion Sensor



FILAMENT HID REPLACEMENT LAMPS

AMMANANTAL PROPERTY.

- **2200K, 3000K, 4000K, 5000K**
- 18, 27, 36, or 80W
- Up to 9,980 Lumens
- Available in E26 or EX39 base

HID **REPLACEMENTS**

LED HID replacements are affordable, practical lighting solutions that provide a quick and easy upgrade for open spaces like warehouses or retail applications.



The LED Retrofit Kits have been designed specifically for existing HID fixtures. They deliver twice the lumen output and efficacy compared to retrofits using generic LED kits.

- 50/100W 3CCT 3000K, 4000K, 5000K
- 180/240W 5000K
- Up to 38,400 Lumens
- Accessories: E26 Mounting Adapter and Surge Protector



250-400W HID replaced with 50W LED retrofit kit. Energy savings up to 87%.

Perfect replacement option for existing fixtures. Shoeboxes, High Bays, Low Bays, Floods, Wall Packs and more.

REPLACEMENT LEDTUBES



INSTANT FIT TYPE ATUBES



naturaLED® Instant-FitType AT5s and T8s make it easy to upgrade fluorescents to energy efficient LED lighting. Compatible with existing electronic fluorescent ballasts without re-wiring, the Instant-Fit tubes come in 2 ft., 3 ft., or 4 ft. lengths and improve energy savings up to 65%. These tubes generate a wide beam spread of 320° like the traditional pattern from existing fluorescent tubes.

- Up to 3,500 Lumens
- 10-28W, 4000K/5000K
- Instant fit (compatible with fluorescent ballast*)
- Instant on, flicker free
- Quick and easy LED upgrade
- Contains no mercury or lead
- Base: 2, 3, 4 ft Mini/Medium Bi-Pin

INTEGRATED TYPE BTUBES

*Contact us for compatibility list.


naturaLED® LED Integrated T5/T8 ULType BTubes work directly with 120-277 line voltage, so it is required to remove the existing fluorescent ballast. This DLC qualified tube is available in 9-40 watts that can replace 2 ft., 3 ft., 4 ft. or 8 ft. tubes. These tubes generate a wide beam spread of 320° like the traditional pattern from existing fluorescent tubes.

- Up to 5,500 Lumens
- 9 40W, 4000K/5000K
- Line Voltage 120-277V
- Instant On, Noise-free









T8 UNIVERSAL





- Compatible with shunted and non-shunted sockets
- Eliminates installation labor costs for additional wiring





- Shunted sockets receive voltage through a single set of wires and spread it to two contacts.
- Non-shunted sockets send voltage to each of the contacts, through two wiring tracks.

Standard Type B Direct Wire tubes use single ended non-shunted socket, but naturaLED® Universal tubes are compatible with shunted and non-shunted, single and double ended as well.

ADDITIONAL PRODUCTS

OUTDOOR LED FIXTURES













INDOOR LED FIXTURES







Linear High Bays



VaporTights


LED **LAMPS**











Filament HID

naturaled°







California, USA

2000 S. Grove Ave, Bldg B, Ontario, CA 91761 855-758-7009 | 909-930-6868

Texas, USA

1940 Diplomat Drive, Farmers Branch, TX 75234

North Carolina, USA

2511 Reliance Ave, Apex, NC 27539

Canada

Unit 206 – 9710 187th Street Surrey, BC V4N 3N6