
PROJECT:

SCHEDULE: **DATE:**

PREPARE BY:

NOTES:

PAR PAR LAMPS & OUTDOOR RATED

DESCRIPTION

naturaLED® PAR LED bulb provides a superior replacement for all incandescent PAR lamp applications. An energy efficient integrated LED driver deliver the same lumen output equivalent with up to 78% energy savings. Our PAR lamps are direct replacement with energy star certification for wet or damp locations. Perfect for display case lighting, track lighting, jewelry lighting and general lighting.



APPLICATIONS

Display Case, Recessed, Accent, General, Residential, Restaurant



Rated Life Hours 25,000
Warranty 5 Years

FEATURES

- Energy star certified
- Damp Location
- Wet Location (outdoor rated)
- UL Listed
- ColorTemp: 3000K, 4000K, 5000K
- Voltage: 120V
- Power Factor: >0.9
- Beam Angle: 40°
- Dimmable
- CRI: >90
- Operating temperature: - 4°F - 104°F
- Instant on / Uniform light distribution and consistent color
- Up to 78% energy savings
- Direct Replacement traditional incandescent design
- Contains no mercury or lead
- Year Warranty
- 25,000 hrs rated average life

SAMPLE NUMBER LED8PAR20/50L/FL/930

STYLE	WATTAGE	SERIES	SHAPE	LUMENS	BEAM ANGLE	CRI/COLOR TEMP
LED	8	PAR	20	50L	FL	930
LED Lighting	8 Watt	PAR Lamp	PAR 20	500 Lumens	Flood	CRI 90 3000K



PAR20,30,30L,38

LAMPS


ORDERING

W=Wet Location / D=Damp Location


Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Base	CRI	Equiv. Wattage (W)	Damp/Wet Location	Energy Star
8	5924	LED8PAR20/50L/FL/930	3000K	500	E26	90	50	D	•
8	5925	LED8PAR20/50L/FL/950	5000K	500	E26	90	50	D	•
10	5926	LED10PAR30/80L/FL/930	3000K	800	E26	90	75	D	•
10.5	5927	LED10PAR30/80L/FL/950	5000K	800	E26	90	75	D	•
10.5	5928	LED10PAR30L/OD/80L/FL/930	3000K	800	E26	90	75	W	•
10.5	5997	LED10PAR30L/OD/80L/FL/940	4000K	800	E26	90	75	W	•
10.5	5929	LED10PAR30L/OD/80L/FL/950	5000K	800	E26	90	75	W	•
15	5930	LED15PAR38/OD/120L/FL930	3000K	1,200	E26	90	100	W	•
15	5998	LED15PAR38/OD/120L/FL940	4000K	1,200	E26	90	100	W	•
15	5931	LED15PAR38/OD/120L/FL950	5000K	1,200	E26	90	100	W	•

DIMENSIONS


PAR20
3.68-oz




PAR30
6.56-oz



PAR30L
7.68-oz




PAR38
12.64-oz



PACKAGE

Case Qty PAR20/30
20 pcs (10 for inner package)



Case Qty PAR38
10 pcs

