

| | | | |
|-------------|-----|------|---------|
| Version | 2.0 | Date | 1/25/19 |
| Prepared By | JC | | |

| PRODUCT SPECIFICATION | |
|-----------------------|--------------------------|
| Category | PL Instant Fit |
| Item Number | 4547 |
| Stock Code | LED12PL/H/100L/4P/835/IF |
| Mounting | G24q / GX24q |
| Housing Color | White / Frosted Lens |



| ELECTRICAL CHARACTERISTICS | | | |
|----------------------------|----------|-------------------------|----|
| Rated Wattage (W) | 12 | Replacement Wattage (W) | 26 |
| Tested Wattage (W) | 12 | | |
| Input Voltage (V) | 120-277V | Surge Protect Level | - |
| Voltage Frequency (Hz) | 50/60 | Dimmable | - |
| Input Current (A) | - | AUX (12V) Line | - |
| Power Factor | >0.9 | | |
| THD | <20% | | |

| PHOTOMETRIC CHARACTERISTICS | | | |
|-----------------------------|-------|----------------|-------|
| Lumen (lm) | 1,050 | CCT (K) | 3500K |
| Efficacy (lm/w) | 88 | Beam Angle (°) | 120° |
| CRI | 80 | | |

| GENERAL CHARACTERISTICS | |
|----------------------------|---------------|
| Operating Temperature (°F) | -4°F ~ 113° |
| Storage Temperature (°F) | -40°F ~ 185° |
| IP Rating | Damp Location |
| IK Rating | - |
| Rated Life (Hrs) | 50,000 |
| Warranty (Yrs) | 5 |

| ACCESSORIES | | |
|-------------|------------|-------------|
| Item # | Stock Code | Description |
| | | |
| | | |
| | | |
| | | |
| | | |

| PRODUCT DIMENSIONS | | |
|----------------------|-------------|--|
| Width- in / (mm) | 6.50" / 165 | |
| Height- in / (mm) | 1.80" / 45 | |
| Depth- in / (mm) | - / - | |
| IK Rating | - | |
| Weight (lbs) | 0.2 | |
| Mounting Height (ft) | - | |
| Cable Length (ft) | - | |

| CERTIFICATIONS | | | |
|--------------------|--------------|------|---|
| UL/ETL | UL | CEC | |
| NSF/ETL Sanitation | | JA8 | |
| Energy Star | | FCC | ✓ |
| DLC | 5.1 Standard | RoHs | ✓ |

| DOCUMENTS | | | |
|-----------|---|-------------|---|
| LM79 | ✓ | IES File | ✓ |
| LM80 | ✓ | Dimmer List | |
| | | | |
| | | | |

| COMMENTS |
|----------|
| |