

Version	2.0	Date	5/2/19
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Wall Pack
Item Number	7099
Stock Code	LED-FXCWP60/50K/DB
Mounting	Wall Mount
Housing Color	Dark Bronze



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	60	Replacement Wattage (W)	250
Tested Wattage (W)	60		
Input Voltage (V)	120-277V	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	-
Input Current (A)	0.66	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	4,700	CCT (K)	5000K
Efficacy (lm/w)	-	Beam Angle (°)	Cut-Off
CRI	>70		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 122°F
Storage Temperature (°F)	-22°F ~ 122°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	3

ACCESSORIES		
Item #	Stock Code	Description
7334	BAEM15-48BC/MV-A	15W CEC Compliant LED Emergency Driver
P10036	SEN-PHO-BT-MT/MV	Photocell 120-277V

PRODUCT DIMENSIONS		
Width- in / (mm)	18" / 457.2	
Height- in / (mm)	9" / 228.6	
Depth- in / (mm)	13.50" / 343	
EPA (ft²)	-	
Weight (lbs)	10.36	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	UL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS