

Version	2.0	Date	6/26/23
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Wall Pack
Item Number	7529
Stock Code	FXTWX60SW/8CCT3/BZ-PHO
Mounting	Wall Mount
Housing Color	Bronze (RAL #8019)



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	25 / 40 / 60	Replacement Wattage (W)	175-400
Tested Wattage (W)	25 / 40 / 60		
Input Voltage (V)	120-277V		
Voltage Frequency (Hz)	50/60	Surge Protect Level	4KV
Input Current (A)	0.67	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%	Photocell	Yes

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	3,125 5,000 7,538	CCT (K)	3CCT (30/40/50K)
Efficacy (lm/w)	126	Beam Angle (°)	115°
CRI	>80	Photocell	Included

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 140°
IP Rating	IP65
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10540	SEN-ANT-11-WH	Motion Sensor 0-10V Internal 12V
P10316	SNE-BRI-RC100	Remote Programmer for P10540
7336	BAEM4-60BC/MV-A	4W LED Emergency Driver 120-277V

PRODUCT DIMENSIONS		
Width- in / (mm)	15.55" / 395	
Height- in / (mm)	9.76" / 248	
Depth- in / (mm)	4.21" / 107	
IK Rating	-	
Weight (lbs)	9.48	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS