

Version	2.0	Date	3/15/19
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Under Cabinet
Item Number	7591
Stock Code	LED-FXUC4/9FR/930
Mounting	Under Cabinet
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	4	Replacement Wattage (W)	13
Tested Wattage (W)	4		
Input Voltage (V)	120V	Surge Protect Level	1KV
Voltage Frequency (Hz)	50/60	Dimmable	Yes
Input Current (A)	0.044	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	260	CCT (K)	3000K
Efficacy (lm/w)	-	Beam Angle (°)	Flood
CRI	>90		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 122°
Storage Temperature (°F)	-4°F ~ 122°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10151	QC-FXUC-10IN	10" Extended Quick Connector
P10152	PWC-FXUC-3FT	3' Power Cable
P10180	QC-FXUC-SRT	Quick Connector

PRODUCT DIMENSIONS		
Width- in / (mm)	9.00" / 229	
Height- in / (mm)	1.00" / 27	
Depth- in / (mm)	3.10" / 79	
IK Rating	-	
Weight (lbs)	0.42	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	UL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	
DLC		RoHs	

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS