

Version	2.0	Date	8/21/19
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Slim Area Light
Item Number	7642
Stock Code	LED-FXSAL360/40K/WH/3S
Mounting	EA6/SB/SF/WM/PM/Yoke Mount
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	360	Replacement Wattage (W)	1000-1500
Tested Wattage (W)	366		
Input Voltage (V)	120-277V	Surge Protect Level	12KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	3.1	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	43,115	CCT (K)	4000K
Efficacy (lm/w)	118	Beam Angle (°)	Type 3
CRI	>70		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 140°F
IP Rating	IP65
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
K141030	REC3PLK/PHO	Photocell

PRODUCT DIMENSIONS		
Width- in / (mm)	14.96" 380	
Height- in / (mm)	3.00" 76.2	
Depth- in / (mm)	21.57" 548	
EPA (ft²)	-	
Weight (lbs)	25.5	
Mounting Height (ft)	-	
Cable Length (ft)	1.97	

CERTIFICATIONS			
UL/ETL	ETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS