

Version	2.0	Date	6/19/23
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Wall Sconce Up/Down
Item Number	7644
Stock Code	FX4DWS20SW/20/8CCT3/BK/347-PH
Mounting	Wall
Housing Color	Black



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	10/20W	Replacement Wattage (W)	100-200
Tested Wattage (W)	-		
Input Voltage (V)	120-347V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.18	AUX (12V) Line	-
Power Factor	>0.9	Photocell	Included

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	2,300	CCT (K)	3CCT (30/40/50K)
Efficacy (lm/w)	115	Beam Angle (°)	20°
CRI	>80	Position	Up/Down Up & Down

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-22°F ~ 140°
IP Rating	IP65
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
Item #		

PRODUCT DIMENSIONS		
Width- in / (mm)	3.33" / 85	
Height- in / (mm)	12" / 297	
Depth- in / (mm)	5" / 124	
EPA (ft²)	-	
Weight (lbs)	2.87	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL,cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star	✓	FCC	✓
DLC		RoHs	

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS