Version	2.0	Date	5/27/24
Prepared By	JC		

PRODUCT SPECIFICATION

Category	Round Canopy
Item Number	7671
Stock Code	FX10RCM29SW/9CCT3/WH
Mounting	Ceiling Mount
Housing Color	White

PICTURE

ELECTRICAL CHARACTERISTICS

Rated Wattage (W)	14 / 22 / 29	Replacement Wattage (W)	150
Tested Wattage (W)	14 / 22 / 29		
Input Voltage (V)	120-277V		
Voltage Frequency (Hz)	50/60	Surge Protect Level	4KV
Input Current (A)	0.26	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%		

PHOTOMETRIC CHARACTERISTICS

Lumen (lm)	1,488 2,339 3,020	CCT (K)	3CCT (30/40/50K)
Efficacy (lm/w)	115	Beam Angle (°)	120°
CRI	>90		

GENERAL CHARACTERISTICS

Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 140°
IP Rating	IP65
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES

Item #	Stock Code	Description
7336	BAEM4-60BC/MV-A	4W Emergency Driver
P10438	SEN-HB001VCR-1	Motion Sensor 0-10V
P10323	SEN-HD05R	Remote Programmer for P10438
P10543	SEN-PHO-JL-412C	Photocell Sensor (small) 120-277V

PRODUCT DIMENSIONS

Width- in / (mm)	3.05"	77.5
Height- in / (mm)	10"	254
Depth- in / (mm)	10"	254
IK Rating	-	
Weight (lbs)	4.6	
Mounting Height (ft)	8~15	
Cable Length (ft)	-	



CERTIFICATIONS

UL/ETL	ETL / cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	
DLC	5.1 Standard	RoHs	✓

DOCUMENTS

LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS