

| | | | |
|-------------|-----|------|---------|
| Version | 2.0 | Date | 8/21/19 |
| Prepared By | JC | | |

| PRODUCT SPECIFICATION | |
|-----------------------|----------------------------|
| Category | Slim Area Light |
| Item Number | 7751 |
| Stock Code | LED-FXSAL360/30K/WH/3S |
| Mounting | EA6/SB/SF/WM/PM/Yoke Mount |
| Housing Color | White |



| ELECTRICAL CHARACTERISTICS | | | |
|----------------------------|----------|-------------------------|-----------|
| Rated Wattage (W) | 360 | Replacement Wattage (W) | 1000-1500 |
| Tested Wattage (W) | 366 | | |
| Input Voltage (V) | 120-277V | Surge Protect Level | 12KV |
| Voltage Frequency (Hz) | 50/60 | Dimmable | 1-10V |
| Input Current (A) | 3.1 | AUX (12V) Line | - |
| Power Factor | >0.9 | | |
| THD | <20% | | |

| PHOTOMETRIC CHARACTERISTICS | | | |
|-----------------------------|--------|----------------|--------|
| Lumen (lm) | 44,796 | CCT (K) | 3000K |
| Efficacy (lm/w) | 122 | Beam Angle (°) | Type 3 |
| CRI | >70 | | |

| GENERAL CHARACTERISTICS | |
|----------------------------|---------------|
| Operating Temperature (°F) | -40°F ~ 122° |
| Storage Temperature (°F) | -40°F ~ 140°F |
| IP Rating | IP65 |
| IK Rating | - |
| Rated Life (Hrs) | 50,000 |
| Warranty (Yrs) | 5 |

| ACCESSORIES | | |
|-------------|-------------|-------------|
| Item # | Stock Code | Description |
| K141030 | REC3PLK/PHO | Photocell |
| | | |
| | | |
| | | |

| PRODUCT DIMENSIONS | | |
|----------------------|------------|--|
| Width- in / (mm) | 14.96" 380 | |
| Height- in / (mm) | 3.00" 76.2 | |
| Depth- in / (mm) | 21.57" 548 | |
| EPA (ft²) | - | |
| Weight (lbs) | 25.5 | |
| Mounting Height (ft) | - | |
| Cable Length (ft) | 1.97 | |

| CERTIFICATIONS | | | |
|--------------------|-----|------|---|
| UL/ETL | ETL | CEC | |
| NSF/ETL Sanitation | | JA8 | |
| Energy Star | | FCC | ✓ |
| DLC | | RoHs | ✓ |

| DOCUMENTS | | | |
|-----------|---|-------------|---|
| LM79 | ✓ | IES File | ✓ |
| LM80 | ✓ | Dimmer List | |
| | | | |
| | | | |

| COMMENTS |
|----------|
| |