

Version	2.0	Date	4/5/2018
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Wall Pack
Item Number	7756
Stock Code	LED-FXTWP28/30K/DB
Mounting	Wall Mount
Housing Color	Dark Bronze



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	28	Replacement Wattage (W)	175
Tested Wattage (W)	28		
Input Voltage (V)	120-277V	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	0.3	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	3,448	CCT (K)	3000K
Efficacy (lm/w)	123	Beam Angle (°)	Forward Throw
CRI	>70		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-22°F ~ 131°F
Storage Temperature (°F)	-22°F ~ 140°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7336	BAEM4-60BC/MV-A	4W CEC Compliant LED Emergency Driver
P10234	SEN-MC605V-D	Microwave Motion Sensor
P10036	SEN-PHO-BT-MT/MV	Photocell

PRODUCT DIMENSIONS		
Width- in / (mm)	8.66" 220	
Height- in / (mm)	7.25" 185	
Depth- in / (mm)	9" 230	
EPA (ft²)	-	
Weight (lbs)	5.51	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79		IES File	✓
LM80	✓	Dimmer List	

COMMENTS