

| | | | |
|-------------|-----|------|--------|
| Version | 2.0 | Date | 8/9/18 |
| Prepared By | JC | | |

| PRODUCT SPECIFICATION | |
|-----------------------|--------------------|
| Category | Floodlight |
| Item Number | 7789 |
| Stock Code | LED-FXFDL10/30K/BK |
| Mounting | Yoke Mount |
| Housing Color | Black |



| ELECTRICAL CHARACTERISTICS | | | |
|----------------------------|----------|-------------------------|-----|
| Rated Wattage (W) | 10 | Replacement Wattage (W) | 100 |
| Tested Wattage (W) | 10.4 | | |
| Input Voltage (V) | 120-277V | Surge Protect Level | 1KV |
| Voltage Frequency (Hz) | 50/60 | Dimmable | - |
| Input Current (A) | 0.1 | AUX (12V) Line | - |
| Power Factor | >0.9 | | |
| THD | <20% | | |

| PHOTOMETRIC CHARACTERISTICS | | | |
|-----------------------------|-------|----------------|-------|
| Lumen (lm) | 1,284 | CCT (K) | 3000K |
| Efficacy (lm/w) | 123 | Beam Angle (°) | Flood |
| CRI | >80 | | |

| GENERAL CHARACTERISTICS | |
|----------------------------|---------------|
| Operating Temperature (°F) | -22°F ~ 131°F |
| Storage Temperature (°F) | -40°F ~ 140°F |
| IP Rating | IP65 |
| Rated Life (Hrs) | 50,000 |
| Warranty (Yrs) | 5 |

| ACCESSORIES | | |
|-------------|------------|-------------|
| Item # | Stock Code | Description |
| | | |
| | | |
| | | |
| | | |
| | | |

| PRODUCT DIMENSIONS | | |
|----------------------|--------------|--|
| Width- in / (mm) | 4.72" / 120 | |
| Height- in / (mm) | 6.37" / 162 | |
| Depth- in / (mm) | 1.53" / 38.8 | |
| EPA (ft²) | - | |
| Weight (lbs) | 1.1 | |
| Mounting Height (ft) | - | |
| Cable Length (ft) | - | |

| CERTIFICATIONS | | | |
|--------------------|-----|------|---|
| UL/ETL | ETL | CEC | |
| NSF/ETL Sanitation | | JA8 | |
| Energy Star | | FCC | ✓ |
| DLC | | RoHs | ✓ |

| DOCUMENTS | | | |
|-----------|---|-------------|---|
| LM79 | ✓ | IES File | ✓ |
| LM80 | ✓ | Dimmer List | |
| | | | |
| | | | |

| COMMENTS |
|----------|
| |