

Version	2.0	Date	11/16/18
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Utility Strip
Item Number	9203
Stock Code	LED-FXUSL64/96FR/50K/MV
Mounting	Surface Mount
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	64	Replacement Wattage (W)	4 x 32W T8
Tested Wattage (W)	60.65		
Input Voltage (V)	120-277V	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	0.704	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	7,943	CCT (K)	5000K
Efficacy (lm/w)	124	Beam Angle (°)	110°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-22°F ~ 113°
Storage Temperature (°F)	-22°F ~ 140°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description

PRODUCT DIMENSIONS		
Width- in / (mm)	96" / 2440	
Height- in / (mm)	3.26" / 82.8	
Depth- in / (mm)	3.11" / 79	
IK Rating	-	
Weight (lbs)	6.92	
Mounting Height (ft)	10~25	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	UL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS