

Version	2.0	Date	5/27/22
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Cut Off Wall Pack
Item Number	9209
Stock Code	LED-FXCWP60/50K/BZ
Mounting	Wall Mount
Housing Color	Bronze



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	60	Replacement Wattage (W)	400
Tested Wattage (W)	62.79		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	0.529	AUX (12V) Line	-
Power Factor	>0.9	Photocell	Included

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	8,425	CCT (K)	5000K
Efficacy (lm/w)	134	Beam Angle (°)	Cut-Off
CRI	>70		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°F
Storage Temperature (°F)	-40°F ~ 176°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7334	BAEM15-48BC/MV-A	15W CEC Compliant LED Emergency Driver
K540380	SEN-ANT-11-WH/BA12V	Microwave Sensor Kit 0-10V
P10316	SEN-BRI-RC100	Remote Programmer for K540380

PRODUCT DIMENSIONS		
Width- in / (mm)	14.20" / 360	
Height- in / (mm)	9.25" / 235	
Depth- in / (mm)	6.50" / 166	
EPA (ft²)	-	
Weight (lbs)	7.05	
Mounting Height (ft)	10~20	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	UL/cUL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS