

Version	2.0	Date	8/21/19
Prepared By	JC		

PRODUCT SPECIFICATION

Category	Slim Area Light
Item Number	9210
Stock Code	LED-FXSAL240/50K/BK/3S
Mounting	EA6/SB/SF/WM/PM/Yoke Mount
Housing Color	Black



ELECTRICAL CHARACTERISTICS

Rated Wattage (W)	240	Replacement Wattage (W)	750-1000
Tested Wattage (W)	242.5		
Input Voltage (V)	120-277V	Surge Protect Level	12KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	2.1	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS

Lumen (lm)	30,015	CCT (K)	5000K
Efficacy (lm/w)	124	Beam Angle (°)	Type 3
CRI	>70		

GENERAL CHARACTERISTICS


Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 140°F
IP Rating	IP65
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES

Item #	Stock Code	Description
K141030	REC3PLK/PHO	Photocell

PRODUCT DIMENSIONS

Width- in / (mm)	14.96" 380
Height- in / (mm)	3.00" 76.2
Depth- in / (mm)	21.57" 548
EPA (ft²)	-
Weight (lbs)	24.5
Mounting Height (ft)	-
Cable Length (ft)	1.97



CERTIFICATIONS

UL/ETL	ETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS

LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS

--