

Version	2.0	Date	9/8/20
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Slim Canopy
Item Number	9212
Stock Code	LED-FXSCM100/50K/BK
Mounting	Ceiling
Housing Color	Black



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	100	Replacement Wattage (W)	>400
Tested Wattage (W)	99.18		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	1.05	AUX (12V) Line	
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	13,022	CCT (K)	5000K
Efficacy (lm/w)	131	Beam Angle (°)	160°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-22°F ~ 131°F
Storage Temperature (°F)	-40°F ~ 140°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7334	BAEM15-48BC/MV-A	15W CEC Compliant LED Emergency Driver
P10234	SEN-MC605V-D	Motion Sensor 0-10V

PRODUCT DIMENSIONS		
Width- in / (mm)	13" / 330	
Height- in / (mm)	4.49" / 114	
Depth- in / (mm)	13" / 330	
EPA (ft²)	-	
Weight (lbs)	8.45	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS