

|             |     |      |        |
|-------------|-----|------|--------|
| Version     | 2.0 | Date | 1/9/19 |
| Prepared By | JC  |      |        |

| PRODUCT SPECIFICATION |                      |
|-----------------------|----------------------|
| Category              | Troffer              |
| Item Number           | 9237                 |
| Stock Code            | LED-FXTF20/2x2/850G1 |
| Mounting              | Ceiling              |
| Housing Color         | White                |



| ELECTRICAL CHARACTERISTICS |          |                         |       |
|----------------------------|----------|-------------------------|-------|
| Rated Wattage (W)          | 20       | Replacement Wattage (W) | 60-70 |
| Tested Wattage (W)         | 20       |                         |       |
| Input Voltage (V)          | 120-277V | Surge Protect Level     | 1KV   |
| Voltage Frequency (Hz)     | 50/60    | Dimmable                | 1-10V |
| Input Current (A)          | 0.17     | AUX (12V) Line          | -     |
| Power Factor               | >0.9     |                         |       |
| THD                        | <20%     |                         |       |

| PHOTOMETRIC CHARACTERISTICS |       |                |       |
|-----------------------------|-------|----------------|-------|
| Lumen (lm)                  | 2,640 | CCT (K)        | 5000K |
| Efficacy (lm/w)             | 132   | Beam Angle (°) | 120°  |
| CRI                         | >80   |                |       |

| GENERAL CHARACTERISTICS    |               |
|----------------------------|---------------|
| Operating Temperature (°F) | -4°F ~ 104°   |
| Storage Temperature (°F)   | -4°F ~ 140°   |
| IP Rating                  | Damp Location |
| IK Rating                  | -             |
| Rated Life (Hrs)           | 50,000        |
| Warranty (Yrs)             | 5             |

| ACCESSORIES |                |                                      |
|-------------|----------------|--------------------------------------|
| Item #      | Stock Code     | Description                          |
| K7334225    | FXTF-BAEM-MT   | Emergency Driver with Mounting Plate |
| K225234     | PLT/FXTF/MC605 | Microwave Motion Sensor              |
|             |                |                                      |
|             |                |                                      |

| PRODUCT DIMENSIONS   |              |  |
|----------------------|--------------|--|
| Width- in / (mm)     | 23.70" / 603 |  |
| Height- in / (mm)    | 23.70" / 603 |  |
| Depth- in / (mm)     | 3.50" / 90   |  |
| IK Rating            | -            |  |
| Weight (lbs)         | 4.1          |  |
| Mounting Height (ft) | 8~10         |  |
| Cable Length (ft)    | -            |  |

| CERTIFICATIONS     |              |      |   |
|--------------------|--------------|------|---|
| UL/ETL             | ETL/cETL     | CEC  |   |
| NSF/ETL Sanitation |              | JA8  |   |
| Energy Star        |              | FCC  | ✓ |
| DLC                | 5.1 Standard | RoHs | ✓ |

| DOCUMENTS |   |             |   |
|-----------|---|-------------|---|
| LM79      | ✓ | IES File    | ✓ |
| LM80      | ✓ | Dimmer List |   |
|           |   |             |   |

| COMMENTS |
|----------|
|          |