naturaled®

Version	2.0	Date	1/9/19
Prepared By	JC		

	PRODUCT	SPI	ECIFI
Category	Troffer		
Item Number	9242		
Stock Code	LED-FXTF45/2x4/840G1		
Mounting	Ceiling		
Housing Color	White		

ICATION	
PICTURE	
PICTORE	

ELECTRICAL CHARACTERISTICS					
Rated Wattage (W)	45		120-130		
Tested Wattage (W)	45	Replacement Wattage (W)			
Input Voltage (V)	120-277V				
Voltage Frequency (Hz)	50/60	Surge Protect Level	1KV		
Input Current (A)	0.4	Dimmable	1-10V		
Power Factor	>0.9	AUX (12V) Line	-		
THD	<20%				

PHOTOMETRIC CHARACTERISTICS					
Lumen (Im) 5,850 (ССТ (К)	4000K		
Efficacy (lm/w)	130	Beam Angle (°)	120°		
CRI	>80				

GENERAL CHARACTERISTICS			
Operating Temperature (°F)	-4°F ~ 104°		
Storage Temperature (°F)	-4°F ~ 140°		
IP Rating	Damp Location		
IK Rating	-		
Rated Life (Hrs)	50,000		
Warranty (Yrs)	5		

ACCESSORIES				
Item #	Stock Code	Description		
K7334225	FXTF-BAEM-MT	Emergency Driver with Mounting Plate		
K225234 PLT/FXTF/MC605 Microwave Motion Sensor		Microwave Motion Sensor		

Width- in / (mm)	47.70"	1212	
Height- in / (mm)	23.70"	603	
Depth- in / (mm)	3.50"	90	
IK Rating		-	
Weight (lbs)	6.5		
Mounting Height (ft)	8~10		
Cable Length (ft)		-	

PRODUCT DIMENSIONS	
0.6in (16mm) ^{eQ} din 200mm 0.8in (20mm) 47.7in (1212mm)	3.5in (90mm) 47in (1195.2mm) 0.3in (8mm) 22.5in (573.3mm) 22.5in (573.3mm) 22.5in (575.3mm) 22.5in (575.3mm) 14.7in (374mm)

CERTIFICATIONS					
UL/ETL	ETL/cETL	CEC		LM79	
NSF/ETL Sanitation		JA8		LM80	
Energy Star		FCC	\checkmark		
DLC	5.1 Standard	RoHs	\checkmark		

	DOCUMENTS				
LM79	\checkmark	IES File	\checkmark		
LM80	\checkmark	Dimmer List			

COMMENTS