

Version	2.0	Date	10/11/21
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Utility Strip
Item Number	9253
Stock Code	LED-FXUSL40/48FR/840/MV-SEN
Mounting	Surface / Ceiling / chain
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	38	Replacement Wattage (W)	2 x 32W T8
Tested Wattage (W)	37.65		
Input Voltage (V)	120-277V	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.34(@120V)	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	5,241	CCT (K)	4000K
Efficacy (lm/w)	138	Beam Angle (°)	110°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 131°
Storage Temperature (°F)	-4°F ~ 131°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7336	BAEM4-60BC/MV-A	4W Emergency Driver
P10303	WG-USL/48/WH	WireGuard

PRODUCT DIMENSIONS		
Width- in / (mm)	48" / 1219	
Height- in / (mm)	2.80" / 73	
Depth- in / (mm)	2.50" / 63.5	
IK Rating	-	
Weight (lbs)	3.85	
Mounting Height (ft)	8~10	
Cable Length (ft)	2	

CERTIFICATIONS			
UL/ETL	ETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS
Motion Sensor Included