

Version	2.0	Date	12/13/19
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Commercial Strip
Item Number	9265
Stock Code	LED-FXCSL42/96FR/840/MV
Mounting	Surface Mount
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	42	Replacement Wattage (W)	4 x 32W T8
Tested Wattage (W)	42.66		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	0.3595	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	6,657	CCT (K)	4000K
Efficacy (lm/w)	159	Beam Angle (°)	Flood
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-22°F ~ 122°
Storage Temperature (°F)	-40°F ~ 158°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7336	BAEM4-60BC/MV-A	4W Emergency Driver
P10234	SEN-MC605V-D	Motion Sensor 0-10V
P10251	WG-CSL/48/WH	Wireguard (Require 2 pcs for 8ft)

PRODUCT DIMENSIONS		
Width- in / (mm)	96" / 2440	
Height- in / (mm)	3.31" / 84	
Depth- in / (mm)	3.25" / 83	
IK Rating	-	
Weight (lbs)	10	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS