

|             |     |      |          |
|-------------|-----|------|----------|
| Version     | 2.0 | Date | 11/30/22 |
| Prepared By | JC  |      |          |

| PRODUCT SPECIFICATION |                          |
|-----------------------|--------------------------|
| Category              | Sport Light              |
| Item Number           | 9323                     |
| Stock Code            | FX16SPL400/33/850/BK/480 |
| Mounting              | Yoke Mount               |
| Housing Color         | Black                    |



| ELECTRICAL CHARACTERISTICS |          |                         |       |
|----------------------------|----------|-------------------------|-------|
| Rated Wattage (W)          | 410      | Replacement Wattage (W) | 1,000 |
| Tested Wattage (W)         | 410      |                         |       |
| Input Voltage (V)          | 277-480V | Surge Protect Level     | 20KV  |
| Voltage Frequency (Hz)     | 50/60    | Dimmable                | 0-10V |
| Input Current (A)          | -        | AUX (12V) Line          | Yes   |
| Power Factor               | >0.9     |                         |       |
| THD                        | <15%     |                         |       |

| PHOTOMETRIC CHARACTERISTICS |        |                |       |
|-----------------------------|--------|----------------|-------|
| Lumen (lm)                  | 61,173 | CCT (K)        | 5000K |
| Efficacy (lm/w)             | 149    | Beam Angle (°) | 3x3   |
| CRI                         | >80    |                |       |

| GENERAL CHARACTERISTICS    |               |
|----------------------------|---------------|
| Operating Temperature (°F) | -40°F ~ 158°F |
| Storage Temperature (°F)   | -40°F ~ 158°F |
| IP Rating                  | IP66          |
| Rated Life (Hrs)           | 50,000        |
| Warranty (Yrs)             | 5             |

| ACCESSORIES |                |  |
|-------------|----------------|--|
| Item #      | Stock Code     | Description                              |
| P10305      | LASER-SPL/GRN  | Laser Light                              |
| P10230      | PWC-300V2-30ft | Black SO Cordd 30ft for 300V 2 Conductor |
| P10307      | MT-SF-16SPL/BK | Slip Fitter Mount                        |
|             |                |  |
|             |                |  |

| PRODUCT DIMENSIONS   |                |  |
|----------------------|----------------|--|
| Width- in / (mm)     | 16" / 404      |  |
| Height- in / (mm)    | 20.6" / 525    |  |
| Depth- in / (mm)     | 14.80" / 375.8 |  |
| EPA (ft²)            | -              |  |
| Weight (lbs)         | 57.3           |  |
| Mounting Height (ft) | 20~40          |  |
| Cable Length (ft)    | 10             |  |

| CERTIFICATIONS     |             |      |   |
|--------------------|-------------|------|---|
| UL/ETL             | ETL/cETL    | CEC  |   |
| NSF/ETL Sanitation |             | JA8  |   |
| Energy Star        |             | FCC  | ✓ |
| DLC                | 5.1 Premium | RoHs | ✓ |

| DOCUMENTS |   |             |   |
|-----------|---|-------------|---|
| LM79      | ✓ | IES File    | ✓ |
| LM80      | ✓ | Dimmer List |   |
|           |   |             |   |

| COMMENTS |
|----------|
|          |