

Version	2.0	Date	9/28/21
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Flush Mount - Modern
Item Number	9357
Stock Code	LED14FMM-180L9CCT5-NI
Mounting	14" Surface
Housing Color	White + Nickel



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	24	Replacement Wattage (W)	150
Tested Wattage (W)	24		
Input Voltage (V)	120V	Surge Protect Level	2KV
Voltage Frequency (Hz)	60	Dimmable	Yes
Input Current (A)	0.18	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	1,800	CCT (K)	5CCT (27/30/35/40/50K)
Efficacy (lm/w)	-	Beam Angle (°)	Flood
CRI	>90		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 104°
Storage Temperature (°F)	-4°F ~ 113°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7337	BAEM25-170BC/347-C	25W Micro Inverter 120-347V with 12" Conduit

PRODUCT DIMENSIONS		
Width- in / (mm)	14.17" / 360	
Height- in / (mm)	3.46" / 88	
Depth- in / (mm)	- / -	
EPA (ft²)	-	
Weight (lbs)	2.49	
Mounting Height (ft)	8~15	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL	CEC	✓
NSF/ETL Sanitation		JA8	✓
Energy Star	✓	FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS