

Version	2.0	Date	9/28/21
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Flush Mount - Disk
Item Number	9440
Stock Code	LED6FMD-110L9CCT5
Mounting	6" Ceiling Mount
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	14	Replacement Wattage (W)	100
Tested Wattage (W)	14		
Input Voltage (V)	120V	Surge Protect Level	2.5KV
Voltage Frequency (Hz)	60	Dimmable	Yes
Input Current (A)	0.12	AUX (12V) Line	-
Power Factor	>0.9		
THD	-		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	1,100	CCT (K)	5CCT (27/30/35/40/50K)
Efficacy (lm/w)	-	Beam Angle (°)	Flood
CRI	>90		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 104°
Storage Temperature (°F)	-4°F ~ 122°
IP Rating	Wet Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7337	BAEM25-170BC/347-C	25W Micro Inverter 120-347V with 12" Conduit

PRODUCT DIMENSIONS		
Width- in / (mm)	7.09"	180
Height- in / (mm)	1.89"	48
Depth- in / (mm)	-	-
EPA (ft²)	-	
Weight (lbs)	1.1	
Mounting Height (ft)	7~10	
Cable Length (ft)	1.31	

CERTIFICATIONS			
UL/ETL	UL/cUL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star	✓	FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS