

|             |     |      |        |
|-------------|-----|------|--------|
| Version     | 2.0 | Date | 2/4/24 |
| Prepared By |     |      |        |

| PRODUCT SPECIFICATION |                     |
|-----------------------|---------------------|
| Category              | Cut Off Wall Pack   |
| Item Number           | 9445                |
| Stock Code            | LED-FXCWP120/40K/BZ |
| Mounting              | Wall Mount          |
| Housing Color         | Bronze              |



| ELECTRICAL CHARACTERISTICS |          |                         |          |
|----------------------------|----------|-------------------------|----------|
| Rated Wattage (W)          | 121      | Replacement Wattage (W) | 575-750  |
| Tested Wattage (W)         | 121.12   |                         |          |
| Input Voltage (V)          | 120-277V | Surge Protect Level     | 6KV      |
| Voltage Frequency (Hz)     | 50/60    | Dimmable                | 0-10V    |
| Input Current (A)          | 1.009    | AUX (12V) Line          | Yes      |
| Power Factor               | >0.9     | Photocell               | Included |

| PHOTOMETRIC CHARACTERISTICS |        |                |         |
|-----------------------------|--------|----------------|---------|
| Lumen (lm)                  | 16,525 | CCT (K)        | 4000K   |
| Efficacy (lm/w)             | 136    | Beam Angle (°) | Cut-Off |
| CRI                         | >70    |                |         |

| GENERAL CHARACTERISTICS    |               |
|----------------------------|---------------|
| Operating Temperature (°F) | -40°F ~ 122°F |
| Storage Temperature (°F)   | -40°F ~ 176°F |
| IP Rating                  | IP65          |
| Rated Life (Hrs)           | 50,000        |
| Warranty (Yrs)             | 5             |

| ACCESSORIES |               |                                     |
|-------------|---------------|-------------------------------------|
| Item #      | Stock Code    | Description                         |
| P10540      | SEN-ANT-11-WH | Microwave Sensor 0-10V, need P10380 |
| P10316      | SEN-BRI-RC100 | Remote Programmer for P10540        |
|             |               |                                     |
|             |               |                                     |

| PRODUCT DIMENSIONS   |              |  |
|----------------------|--------------|--|
| Width- in / (mm)     | 14.20" / 360 |  |
| Height- in / (mm)    | 9.25" / 235  |  |
| Depth- in / (mm)     | 9.60" / 245  |  |
| EPA (ft²)            | -            |  |
| Weight (lbs)         | 10.56        |  |
| Mounting Height (ft) | 15~25        |  |
| Cable Length (ft)    | -            |  |

| CERTIFICATIONS     |             |      |   |
|--------------------|-------------|------|---|
| UL/ETL             | UL/cUL      | CEC  |   |
| NSF/ETL Sanitation |             | JA8  |   |
| Energy Star        |             | FCC  | ✓ |
| DLC                | 5.1 Premium | RoHs | ✓ |

| DOCUMENTS |   |             |   |
|-----------|---|-------------|---|
| LM79      | ✓ | IES File    | ✓ |
| LM80      | ✓ | Dimmer List |   |
|           |   |             |   |

| COMMENTS |
|----------|
|          |