

Version	2.0	Date	4/9/20
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Backlit Panel
Item Number	9461
Stock Code	FXPNL50/2x4/8CCT3
Mounting	Recessed
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	50	Replacement Wattage (W)	120-130
Tested Wattage (W)	50		
Input Voltage (V)	120-277V	Surge Protect Level	2.5KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.46 (@120V)	AUX (12V) Line	-
Power Factor	>0.9		
THD	-		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	5,900	CCT (K)	3CCT (35/40/50K)
Efficacy (lm/w)	118	Beam Angle (°)	115°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 104°
Storage Temperature (°F)	-4°F ~ 176°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7338	BAEM8L-60BC/347-A	8W LED Emergency Driver 120-347V with 12" Conduit

PRODUCT DIMENSIONS		
Width- in / (mm)	48" / 1212	
Height- in / (mm)	24" / 603	
Depth- in / (mm)	1.79" / 45.5	
IK Rating	-	
Weight (lbs)	8.82	
Mounting Height (ft)	8~20	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS