

Version	2.0	Date	10/23/20
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Downlight
Item Number	9526
Stock Code	LED4RL10-75L9CCT5
Mounting	4" Recessed
Housing Color	White




ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	10	Replacement Wattage (W)	80
Tested Wattage (W)	10		
Input Voltage (V)	120V	Surge Protect Level	1.5KV
Voltage Frequency (Hz)	60	Dimmable	Yes
Input Current (A)	0.1	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	750	CCT (K)	5CCT (27/30/35/40/50K)
Efficacy (lm/w)	-	Beam Angle (°)	Flood
CRI	>90		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	5°F ~ 104°
Storage Temperature (°F)	14°F ~ 104°
IP Rating	Wet Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10170	RT-4RL9-BK	Black Round Trim
P10171	RT-4RL9-CH	Chrome Round Trim
P10172	RT-4RL9-CH-WH	White/Chrome Round Trim
P10176	RTS-4RL-WH	White Square Trim
7337	BAEM25-170BC/347-C	25W Micro Inverter 120-347V with 12" Conduit

PRODUCT DIMENSIONS		
Width- in / (mm)	5.09"	129
Height- in / (mm)	3.11"	79
Depth- in / (mm)	5.09"	129
EPA (ft²)	-	
Weight (lbs)	0.6	
Mounting Height (ft)	-	
Cable Length (ft)	-	



CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	✓
NSF/ETL Sanitation		JA8	✓
Energy Star	✓	FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS