

Version	2.0	Date	10/23/20
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Downlight
Item Number	9527
Stock Code	LED6RL14-110L9CCT5
Mounting	5/6" Recessed
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	14	Replacement Wattage (W)	120
Tested Wattage (W)	14		
Input Voltage (V)	120V	Surge Protect Level	1.5KV
Voltage Frequency (Hz)	60	Dimmable	Yes
Input Current (A)	0.125	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	1,100	CCT (K)	5CCT (27/30/35/40/50K)
Efficacy (lm/w)	-	Beam Angle (°)	Flood
CRI	S		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	5°F ~ 104°
Storage Temperature (°F)	14°F ~ 104°
IP Rating	Wet Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10173	RT-6RL15-BK	Black Round Trim
P10174	RT-6RL15-CH	Chrome Round Trim
P10175	RT-6RL15-CH-WH	Chrome/White Round Trim
P10177	RTS-6RL15-WH	Square White Trim
7337	BAEM25-170BC/347-C	25W Micro Inverter 120-347V with 12" Conduit

PRODUCT DIMENSIONS		
Width- in / (mm)	7.30" / 186	
Height- in / (mm)	3.22" / 82	
Depth- in / (mm)	7.30" / 186	
EPA (ft²)	-	
Weight (lbs)	1.6	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	✓
NSF/ETL Sanitation		JA8	✓
Energy Star	✓	FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS