

Version	2.0	Date	6/26/24
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Compact Area Light
Item Number	9531
Stock Code	CAL/300S/T3/C3/BZ-Z10
Mounting	Pole Mount/ Slip Fitter/ Yoke Mount
Housing Color	Bronze (RAL#8019)



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	200/240/300	Replacement Wattage (W)	1000-1500
Tested Wattage (W)	300.52		
Input Voltage (V)	120-277V	Surge Protect Level	6KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	2.75(@120V)	AUX (12V) Line	Connect with Z10 Receptacle
Power Factor	>0.9	Z10 Receptacle	Yes
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	26,000 32,491 40,397	CCT (K)	CCT3 (30/40/50K)
Efficacy (lm/w)	-	Beam Angle (°)	Type 3
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	- 40°F ~ 113°
Storage Temperature (°F)	- 40°F ~ 158°F
IP Rating	IP65
IK Rating	IK10
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10519	REC-Z10-BK	Z10 Base with black cap (Included)
P10367	MT-CAL/YK13/BZ	13" Yoke Mount (Bronze)
P10366	MT-CAL/SF/BZ	Slip Fitter (Bronze)
P10365	MT-CAL/PM8/BZ	8" Pole Mount (Bronze)

*See page 2 for more Accessories

PRODUCT DIMENSIONS		
Width- in / (mm)	12.39" / 315	
Height- in / (mm)	2.42" / 61	
Depth- in / (mm)	22.72" / 577	
EPA (ft²)	0.56	
Weight (lbs)	12.3	
Mounting Height (ft)	15~30	
Cable Length (ft)	6	

CERTIFICATIONS			
UL/ETL	UL/cUL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS

Version	2.0	Date	6/26/24
Prepared By	JC		

ACCESSORIES		
Item #	Stock Code	Description
K473478	MT-CAL/WM/BZ	Wall Mount Kit - Bronze
P10398	LENS-CAL-IV	Type IV Lens
P10399	LENS-CAL-V	Type V Lens
P10405	GSFB-CAL/BZ	Glare Shield
P10520	SEN-ANT-5-Z10-PC	Z10 Photocell
P10521	SEN-ANT-5-Z10	Z10 Microwave Sensor with Photocell
P10522	SEN-ANT-6-Z10	Z10 PIR Sensor with Photocell
P10316	SEN-BRI-RC100	Remote Controller for P10521/P10522
P10389	SPD-L-10KV-277	10KV Surge Protector 120-277V
P10390	SPD-L-20KV-277	20KV Surge Protector 120-277V
K141030	REC3PLK/PHO	Photocell Kit (P10141+P10030)
P10142	REC7PLK	7-Prong Twist Lock Receptacle
P10053	SEN-PHO-LK-MT-SRT	Shorting Cap