

Version	2.0	Date	2/12/24
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Linear Architectural Light
Item Number	9549
Stock Code	FXLAL60SW/48FR/8CCT5/WH/347
Mounting	Pendant Mount/ Ceiling Mount/ Wall Mount/Recessed Mount
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	30/35/40/50/60	Replacement Wattage (W)	100-300
Tested Wattage (W)	30/35/40/50/60		
Input Voltage (V)	120-347V		
Voltage Frequency (Hz)	50/60	Surge Protect Level	4KV
Input Current (A)	0.55	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%	Photocell	-

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	30W: 3,780 35W: 4,410 40W: 5,040 50W: 6,300 60W: 7,560	CCT (K)	5CCT (3000/3500/4000/5000/6500K)
	Efficacy (lm/w)		Beam Angle (°)
		3000K:126lm/W 3500K:133lm/W 4000K:137lm/W 5000K:137lm/W 6500K:131lm/W	
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 122°F
Storage Temperature (°F)	-40°F ~ 176°F
IP Rating	IP20
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7336	BAEM4-60BC/MV-A	4W Emergency Driver 120-277V
P10549	LM-2.5LAL/48/WH	4-ft Uplight Bar 8CCT5 - White
P10438	SEN-HB001VCR-1	12V Motion Sensor 0-10V Dimming
P10547	CNTR-2.5LAL/KIT	Linkable Connector Kit
P10552	CNTR-2.5LAL/L/WH	L Shape Linear Architectural Light 8CCT5-White
P10553	CNTR-2.5LAL/T/WH	T Shape Linear Architectural Light 8CCT5-White
P10554	CNTR-2.5LAL/X/WH	X Shape Linear Architectural Light 8CCT5-White

PRODUCT DIMENSIONS		
Length- in / (mm)	47.24" 1204	
Height- in / (mm)	3.14" 80	
Width- in / (mm)	2.55" 65	
EPA (ft²)	-	
Weight (lbs)	3.96	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS