

Version	2.0	Date	1/16/24
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Cut Off Wall Pack
Item Number	9553
Stock Code	FXCWP60SW/CCT3/BZ-PHO
Mounting	Wall
Housing Color	Bronze



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	28/40/60	Replacement Wattage (W)	100-250
Tested Wattage (W)	63.69		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.537	AUX (12V) Line	No
Power Factor	>0.9	Photocell	Included
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	3,780 5,400 8,176	CCT (K)	3CCT (30/40/50K)
Efficacy (lm/w)	136	Beam Angle (°)	Cut Off
CRI	>70		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 176°
IP Rating	IP65
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7334	BAEM15-48BC/MV-A	15W Emergency Battery Backup Driver
K540380	SEN-ANT-11-WH/BA12V	Microwave Sensor Kit 0-10V
P10316	SEN-BRI-RC100	Remote Programmer for P10540
P10380	BA-BQE03-0250-12	120-347V to 12 V Power supply (no relay)

PRODUCT DIMENSIONS		
Width- in / (mm)	14.20" / 360	
Height- in / (mm)	9.25" / 235	
Depth- in / (mm)	6.50" / 166	
EPA (ft²)	-	
Weight (lbs)	7.05	
Mounting Height (ft)	10~20	
Cable Length (ft)	1.98	

CERTIFICATIONS			
UL/ETL	UL/cUL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS