

Version	2.0	Date	11/24/21
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Vapor Tight
Item Number	9561
Stock Code	FXVTL30SW/24FR/8CCT3
Mounting	Surface / Ceiling / Chain
Housing Color	Gray + Frosted Lens



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	20 / 25 / 30	Replacement Wattage (W)	2 x 32W T8
Tested Wattage (W)	30		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.27 (@120V)	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	2,613 3,250 4,156	CCT (K)	3CCT (35/40/50K)
Efficacy (lm/w)	139	Beam Angle (°)	110°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 158°
IP Rating	IP66
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
K7336412	FXVTL30-BAEM-MTG1	Emergency Driver Kit
K438380	SEN-HB001VCR/BA12V	Motion Sensor 0-10V Bi-Level Internal
P10323	SEN-HD06R	Remote Programmer
P10411	MT-Linear-45/90	45°/90° Angle Mount Bracket

PRODUCT DIMENSIONS		
Width- in / (mm)	23.62" / 600	
Height- in / (mm)	3.70" / 94	
Depth- in / (mm)	5.00" / 127	
IK Rating	-	
Weight (lbs)	2.65	
Mounting Height (ft)	7~8	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL	CEC	
NSF/ETL Sanitation	✓	JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS