

Version	2.0	Date	3/3/22
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Floodlight
Item Number	9567
Stock Code	FXFDL150SW/66/40K/BZ-YK
Mounting	Yoke Mount
Housing Color	Bronze (RAL#8019)



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	100 / 130 / 150	Replacement Wattage (W)	400
Tested Wattage (W)	150		
Input Voltage (V)	120-277V	Surge Protect Level	6KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	1.375 (@120V)	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	13,500 16,900 20,890	CCT (K)	4000K
Efficacy (lm/w)	90	Beam Angle (°)	6x6
CRI	>70		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	- 40°F ~ 113°F
Storage Temperature (°F)	- 40°F ~ 158°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
K141030	REC3PLK/PHO	Photocell Kit (P10141+P10030)
P10414	MT-FDL/SF/BZ	Slip Fitter Mount
P10389	SPD-L-10KV-277	10KV Surge Protector 120-277V
P10390	SPD-L-20KV-277	20KV Surge Protector 120-277V

PRODUCT DIMENSIONS		
Width- in / (mm)	15.20" / 386	
Height- in / (mm)	11.48" / 292	
Depth- in / (mm)	3.27" / 83	
EPA (ft²)	-	
Weight (lbs)	9.5	
Mounting Height (ft)	10~26	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	UL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS