

Version	2.0	Date	6/24/21
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Post Top
Item Number	9572
Stock Code	FX15PST100SW/8CCT3/BK
Mounting	Pole - Fits 2 3/8" - 3 Tenon
Housing Color	Black



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	60 / 80 / 100	Replacement Wattage (W)	250
Tested Wattage (W)	100		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.83 (@120V)	AUX (12V) Line	-
Power Factor	>0.9	Photocell	Included

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	8,104 10,400 13,361	CCT (K)	3CCT (30/40/50K)
Efficacy (lm/w)	134	Beam Angle (°)	110°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°F
Storage Temperature (°F)	-40°F ~ 158°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10389	SPD-L-10KV-277	10KV Surge Protector 120-277V
P10390	SPD-L-20KV-277	20KV Surge Protector 120-277V

PRODUCT DIMENSIONS		
Width- in / (mm)	15" / 380	
Height- in / (mm)	21.6" / 550	
Depth- in / (mm)	2.5" / 63.5	
EPA (ft²)	0.582	
Weight (lbs)	8.8	
Mounting Height (ft)	8~15	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79		IES File	✓
LM80	✓	Dimmer List	

COMMENTS
Selectable Wattages Photocell Sensor On/Off Switch