

Version	2.0	Date	11/3/21
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Commercial Strip
Item Number	9575
Stock Code	FXCSL44SW/48FR/8CCT3/MV
Mounting	Surface Mount
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	22 / 28 / 36 / 44	Replacement Wattage (W)	3 x 32W T8
Tested Wattage (W)	22 / 28 / 36 / 44		
Input Voltage (V)	120-277V	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.4 (@120V)	AUX (12V) Line	Yes
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	2,970	CCT (K)	3CCT (35/40/50K)
	3,640		
	4,680		
	5,724		
Efficacy (lm/w)	141	Beam Angle (°)	Flood
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-13°F ~ 104°
Storage Temperature (°F)	-13°F ~ 176°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10438	SEN-HB001VCR-1	Motion Sensor
P10323	SEN-HD06R	Remote Programmer for P10438
P10011	WG-2.5CSL/48/WH	WireGuard
7336	BAEM4-60BC/MV-A	4W Emergency Driver

PRODUCT DIMENSIONS		
Width- in / (mm)	46.60" / 1184	
Height- in / (mm)	2.71" / 69	
Depth- in / (mm)	2.58" / 66	
IK Rating	-	
Weight (lbs)	4.68	
Mounting Height (ft)	10~25	
Cable Length (ft)	2	

CERTIFICATIONS			
UL/ETL	UL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS