

|             |     |      |          |
|-------------|-----|------|----------|
| Version     | 2.0 | Date | 12/31/21 |
| Prepared By | JC  |      |          |

| PRODUCT SPECIFICATION |                        |
|-----------------------|------------------------|
| Category              | Commercial Strip       |
| Item Number           | 9577                   |
| Stock Code            | FXCSL22/24FR/8CCT3/347 |
| Mounting              | Surface Mount          |
| Housing Color         | White                  |



| ELECTRICAL CHARACTERISTICS |              |                         |            |
|----------------------------|--------------|-------------------------|------------|
| Rated Wattage (W)          | 22           | Replacement Wattage (W) | 2 x 17W T8 |
| Tested Wattage (W)         | 22           |                         |            |
| Input Voltage (V)          | 120-347V     | Surge Protect Level     | 2KV        |
| Voltage Frequency (Hz)     | 50/60        | Dimmable                | 0-10V      |
| Input Current (A)          | 0.36 (@120V) | AUX (12V) Line          | Yes        |
| Power Factor               | >0.9         |                         |            |
| THD                        | <20%         |                         |            |

| PHOTOMETRIC CHARACTERISTICS |       |                |                  |
|-----------------------------|-------|----------------|------------------|
| Lumen (lm)                  | 2,878 | CCT (K)        | 3CCT (35/40/50K) |
| Efficacy (lm/w)             | 131   | Beam Angle (°) | 110°             |
| CRI                         | >80   |                |                  |

| GENERAL CHARACTERISTICS    |               |
|----------------------------|---------------|
| Operating Temperature (°F) | -13°F ~ 104°  |
| Storage Temperature (°F)   | -13°F ~ 176°  |
| IP Rating                  | Damp Location |
| IK Rating                  | -             |
| Rated Life (Hrs)           | 50,000        |
| Warranty (Yrs)             | 5             |

| ACCESSORIES |                 |                              |
|-------------|-----------------|------------------------------|
| Item #      | Stock Code      | Description                  |
| P10438      | SEN-HB001VCR-1  | Motion Sensor                |
| P10323      | SEN-HD06R       | Remote Programmer for P10438 |
| P10010      | WG-2.5CSL/24/WH | WireGuard                    |
|             |                 |                              |
|             |                 |                              |

| PRODUCT DIMENSIONS   |            |  |
|----------------------|------------|--|
| Length- in / (mm)    | 24.02" 610 |  |
| Height- in / (mm)    | 2.71" 69   |  |
| Depth- in / (mm)     | 2.58" 66   |  |
| IK Rating            | -          |  |
| Weight (lbs)         | 2.91       |  |
| Mounting Height (ft) | 10~25      |  |
| Cable Length (ft)    | 2          |  |

| CERTIFICATIONS     |              |      |   |
|--------------------|--------------|------|---|
| UL/ETL             | UL           | CEC  |   |
| NSF/ETL Sanitation |              | JA8  |   |
| Energy Star        |              | FCC  | ✓ |
| DLC                | 5.1 Standard | RoHs | ✓ |

| DOCUMENTS |   |             |   |
|-----------|---|-------------|---|
| LM79      | ✓ | IES File    | ✓ |
| LM80      | ✓ | Dimmer List |   |
|           |   |             |   |
|           |   |             |   |

| COMMENTS |
|----------|
|          |