

Version	1.0	Date	6/26/24
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Troffer
Item Number	9586
Stock Code	FXTF36SW/2X2/8CCT3G1
Mounting	Ceiling
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	20 /30 / 36	Replacement Wattage (W)	60-100
Tested Wattage (W)	36		
Input Voltage (V)	120-277V	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.34	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	2,640	CCT (K)	3CCT (35/40/50K)
	3,900		
	4,572		
Efficacy (lm/w)	127	Beam Angle (°)	115°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 104°
Storage Temperature (°F)	-4°F ~ 140°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
K7336593	FXTFSW-BAEM-MT-G1	Emergency Driver Kit
K234593	FXTFSW/MC605-MT-G1	Motion Sensor Kit
P10417	MT-2X2BOX-3.0IN	3.0" Height 2x2 Surface Mount
P10335	MT-2x2BOX-4.5in	4.5" Height 2x2 Surface Mount
P10228	MT-2X2FMBOX	2x2 Flange Mount Kit

PRODUCT DIMENSIONS		
Width- in / (mm)	23.70" 603	
Height- in / (mm)	23.70" 603	
Depth- in / (mm)	1.97" 50	
IK Rating	-	
Weight (lbs)	8	
Mounting Height (ft)	8~10	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS