

Version	2.0	Date	8/6/24
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Full Cutoff Wall Pack
Item Number	9707
Stock Code	CWX/40S/8C3/WH-PHO
Mounting	Wall Mount
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	15 / 28 / 40	Replacement Wattage (W)	250
Tested Wattage (W)	-		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60		
Input Current (A)	0.36	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%	Photocell	Yes

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	2,600	CCT (K)	3 CCT (30/40/50K)
	3,640		
	5,200		
Efficacy (lm/w)	130	Beam Angle (°)	90°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 176°
IP Rating	IP65
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
		4W CEC-Compliant LED Emergency Driver 120-277V
7336	BAEM4-60BC/MV-A	
P10540	SEN-ANT-11-WH	Sensor 12V Microwave 0-10V, need P10380
P10518	REC-Z10-WH	Z10 Receptacle Base w/ White Cap
P10521	SEN-ANT-5-Z10	Z10 Base Microwave Sensor w/Photocell
P10522	SEN-ANT-6-Z10	Z10 Base PIR Sensor w/Photocell
P10316	SEN-BRI-RC100	Remote Programmer for P10540/P10521/P10522

PRODUCT DIMENSIONS		
Width- in / (mm)	9.4" 240	
Height- in / (mm)	6.2" 158	
Depth- in / (mm)	3.5" 90.2	
IK Rating	-	
Weight (lbs)	4.63	
Mounting Height (ft)	7~15	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS