

Version	1.0	Date	5/30/24
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Vapor Tight Slim
Item Number	9709
Stock Code	VTL4/25S/24FR/8C3
Mounting	Ceiling Mount
Housing Color	Gray + PC Lens



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	15 / 20 / 25	Replacement Wattage (W)	2 x 32W T8
Tested Wattage (W)	-		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.23 (@120V)	AUX (12V) Line	Yes
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	2,175 2,900 3,625	CCT (K)	3CCT (35/40/50K)
Efficacy (lm/w)	145	Beam Angle (°)	120°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 176°
IP Rating	IP65
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7336	BAEM4-60BC/MV-A	4W Emergency Batter
P10590	SEN-HD027VCR	Programmable Motion Sensor
P10323	SEN-HD06R	Remote Programmer

PRODUCT DIMENSIONS		
Width- in / (mm)	22.8" / 580	
Height- in / (mm)	3.90" / 98.2	
Depth- in / (mm)	3.0" / 76.7	
IK Rating	-	
Weight (lbs)	-	
Mounting Height (ft)	7~8	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL, cETLus	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS