

| | | | |
|-------------|-----|------|---------|
| Version | 2.0 | Date | 4/26/19 |
| Prepared By | JC | | |

| PRODUCT SPECIFICATION | |
|-----------------------|-----------------------|
| Category | LED Candelabra |
| Item Number | 4564 |
| Stock Code | LED4.5CAB/32L/E12/850 |
| Mounting | E12 |
| Housing Color | White + Clear Glass |




| ELECTRICAL CHARACTERISTICS | | | |
|----------------------------|------|-------------------------|-----|
| Rated Wattage (W) | 4.5 | Replacement Wattage (W) | 40 |
| Tested Wattage (W) | 4.5 | | |
| Input Voltage (V) | 120V | Surge Protect Level | - |
| Voltage Frequency (Hz) | 60 | | |
| Input Current (A) | 0.06 | Dimmable | Yes |
| Power Factor | >0.9 | AUX (12V) Line | - |
| THD | - | | |

| PHOTOMETRIC CHARACTERISTICS | | | |
|-----------------------------|-----|----------------|-------|
| Lumen (lm) | 325 | CCT (K) | 5000K |
| Efficacy (lm/w) | 72 | Beam Angle (°) | - |
| CRI | 80 | | |

| GENERAL CHARACTERISTICS | |
|----------------------------|---------------|
| Operating Temperature (°F) | -4°F ~ 104° |
| Storage Temperature (°F) | -4°F ~ 140° |
| IP Rating | Damp Location |
| IK Rating | - |
| Rated Life (Hrs) | 25,000 |
| Warranty (Yrs) | 3 |

| ACCESSORIES | | |
|-------------|------------|-------------|
| Item # | Stock Code | Description |
| | | |
| | | |
| | | |
| | | |
| | | |

| PRODUCT DIMENSIONS | | |
|----------------------|--------|------|
| Width- in / (mm) | 1.40" | 35.5 |
| Height- in / (mm) | 3.84" | 97.4 |
| Depth- in / (mm) | - | - |
| IK Rating | - | - |
| Weight (lbs) | 1.13oz | |
| Mounting Height (ft) | - | |
| Cable Length (ft) | - | |



| CERTIFICATIONS | | | |
|--------------------|----|------|---|
| UL/ETL | UL | CEC | ✓ |
| NSF/ETL Sanitation | | JA8 | ✓ |
| Energy Star | ✓ | FCC | ✓ |
| DLC | | RoHs | ✓ |

| DOCUMENTS | | | |
|-----------|---|-------------|---|
| LM79 | ✓ | IES File | ✓ |
| LM80 | ✓ | Dimmer List | |
| | | | |
| | | | |

| COMMENTS |
|----------|
| |