

	Product	Spec	
Category	LED Bulkhead Wall Light		
Item Code	7024		
Stock Code	LED-FXBWL10/830/BK	PICTURE	
Mounting	Wall Mounted		
Housing Color	Black aluminum housing + frosted glass lens		

Electric	c Characteristics	Photometric C	haracteristics
Rated Wattage (W)	10	Lumen (lm)	700
Tested Wattage (W)	10	Efficacy (lm/w)	70
Input Voltage (V)	100~277	CRI	80
Voltage Frequency (Hz)	50/60	сст (к)	3000
nput Current (A)	0.1	Beam Angle (∘)	130
Power Factor	>0.9	General Characteristics	
Replacement Wattage (W)	90W	Operating Temperature -4°F~104°F	
Surge protect level	-	Storage Temperature	-4°F~122°F
Dimmable	No	IP rating	UL Wet Location
THD	-	Rated Life	50000 hrs.
		Warranty	5 years
Produ	act Dimensions	Suggested A	Accessory
Weight (lbs.)	3.53		
Height (in)	5.55		
Height (in) Length (in)			
	5.55		
Length (in)	5.55 11.26		
Length (in) Width (in)	5.55 11.26		
Length (in) Width (in) Mounting Height (ft.)	5.55 11.26		
Length (in) Width (in) Mounting Height (ft.)	5.55 11.26	cations	
Length (in) Width (in) Mounting Height (ft.)	5.55 11.26 7.09	cations LM79	√
Length (in) Width (in) Mounting Height (ft.) Cable Length (ft.)	5.55 11.26 7.09 Qualific		V V
Length (in) Width (in) Mounting Height (ft.) Cable Length (ft.) UL/ETL Energy Star	5.55 11.26 7.09 Qualifie	LM79	
Length (in) Width (in) Mounting Height (ft.) Cable Length (ft.) UL/ETL Energy Star	5.55 11.26 7.09 Qualifie	LM79 LM80	٧
Length (in) Width (in) Mounting Height (ft.) Cable Length (ft.) UL/ETL Energy Star DLC CEC	5.55 11.26 7.09 Qualifie	LM79 LM80 IES File	٧
Length (in) Width (in) Mounting Height (ft.) Cable Length (ft.)	5.55 11.26 7.09 Qualifie	LM79 LM80 IES File FDA	٧