

Version	1.0	Date	7/7/23
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Retrofit Strip
Item Number	7162
Stock Code	FXRSL68SW/96FR/8CCT3/MV
Mounting	Linear Ceiling Retrofit
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	44 / 58 / 68	Replacement Wattage (W)	4 x 32W T8
Tested Wattage (W)			
Input Voltage (V)	120-277V	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.36	AUX (12V) Line	Yes
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	5,720 7,450 8,840	CCT (K)	3CCT (35/40/50K)
Efficacy (lm/w)	130	Beam Angle (°)	Flood
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-13°F ~ 104°
Storage Temperature (°F)	-13°F ~ 176°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10438	SEN-HB001VCR-1	Motion Sensor 0-10V
7334	BAEM15-48BC/MV-A	15W Emergency Driver
P10323	SEN-HD05R	Remote Programmer

PRODUCT DIMENSIONS		
Length- in / (mm)	95.44" / 2424.2	
Height- in / (mm)	2.35" / 59.9	
Width- in / (mm)	5.82" / 147.9	
IK Rating	-	
Weight (lbs)	9.46	
Mounting Height (ft)	10~25	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	UL / cUL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS