

Version	2.0	Date	8/15/18
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Floodlight
Item Number	7179
Stock Code	LED-FXFDL29/40K/DB-KNC
Mounting	1/2" Knuckle Mount
Housing Color	Dark Bronze



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	29	Replacement Wattage (W)	175
Tested Wattage (W)	29.5		
Input Voltage (V)	120-277	Surge Protect Level	-
Voltage Frequency (Hz)	50/60	Dimmable	-
Input Current (A)	0.4	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	3,521	CCT (K)	4000K
Efficacy (lm/w)	119	Beam Angle (°)	Flood
CRI	>70		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-22°F ~ 122°F
Storage Temperature (°F)	-22°F ~ 122°F
IP Rating	IP66
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10036	SEN-PHO-BT-MT/MV	Button Photocell 120-277V

PRODUCT DIMENSIONS		
Width- in / (mm)	9.00" 228.6	
Height- in / (mm)	11.75" 298.5	
Depth- in / (mm)	7.00" 177.8	
EPA (ft²)	-	
Weight (lbs)	7	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	UL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC		RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS