

Version	2.0	Date	8/17/23
Prepared By	JC		

PRODUCT SPECIFICATION			
Category	Slim Area Light		
Item Number	7653		
Stock Code	FXSAL150SW/840/WH/T3		
Mounting	Pole Mount/ Slip Fitter/ Yoke Mount/ Wall Mount		
Housing Color	White (RAL#9003)		
PICTURE			

ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	90 / 120 / 150	Replacement Wattage (W)	400-575
Tested Wattage (W)	-		
Input Voltage (V)	120-277V	Surge Protect Level	10KV
Voltage Frequency (Hz)	50/60		
Input Current (A)	1.36	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	12,649	CCT (K)	4000K
	16,800		
	21,163		
Efficacy (lm/w)	141	Beam Angle (°)	Type 3
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°
Storage Temperature (°F)	-40°F ~ 140°F
IP Rating	IP66
IK Rating	IK08
Rated Life (Hrs)	50,000
Warranty (Yrs)	7

ACCESSORIES		
Item #	Stock Code	Description
P10371	SEN-BRI619	PIR Motion/Photocell 0-10V Internal 12V Low Voltage for 347/480V
P10316	SEN-BRI-RC100	Remote Programmer for P10371
K141030	REC3PLK/PHO	Twist-Lock Photocell and Receptacle Mount 120-277V 3 Prong

PRODUCT DIMENSIONS		
Width- in / (mm)	12.01"	307
Height- in / (mm)	2.60"	66
Depth- in / (mm)	14.20"	360
EPA (ft²)	0.212 ft² (@ 0 deg)	
Weight (lbs)	8	
Mounting Height (ft)	10~15	
Cable Length (ft)	1.64	

Technical drawings of the Slim Area Light showing front, side, and top views with dimensions:

- Front view: Shows the light fixture with two rectangular light panels. Dimensions: 12.01in (307mm) width, 2.6in (66mm) height.
- Side view: Shows the light fixture from the side. Dimensions: 14.2in (360mm) depth.
- Top view: Shows the light fixture from above. Dimensions: 12.01in (307mm) width, 2.6in (66mm) height.

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS