

|             |     |      |         |
|-------------|-----|------|---------|
| Version     | 2.0 | Date | 6/19/23 |
| Prepared By | JC  |      |         |

| PRODUCT SPECIFICATION |                      |
|-----------------------|----------------------|
| Category              | Round Canopy         |
| Item Number           | 7670                 |
| Stock Code            | FX10RCM29SW/9CCT3/DB |
| Mounting              | Ceiling Mount        |
| Housing Color         | Dark Bronze          |



| ELECTRICAL CHARACTERISTICS |              |                         |       |
|----------------------------|--------------|-------------------------|-------|
| Rated Wattage (W)          | 14 / 22 / 29 | Replacement Wattage (W) | 150   |
| Tested Wattage (W)         | 14 / 22 / 29 |                         |       |
| Input Voltage (V)          | 120-277V     |                         |       |
| Voltage Frequency (Hz)     | 50/60        | Surge Protect Level     | 4KV   |
| Input Current (A)          | 0.27         | Dimmable                | 0-10V |
| Power Factor               | >0.9         | AUX (12V) Line          | Yes   |
| THD                        | <20%         |                         |       |

| PHOTOMETRIC CHARACTERISTICS |                         |                |                  |
|-----------------------------|-------------------------|----------------|------------------|
| Lumen (lm)                  | 1,610<br>2,530<br>3,335 | CCT (K)        | 3CCT (30/40/50K) |
| Efficacy (lm/w)             | 115                     | Beam Angle (°) | 120°             |
| CRI                         | >90                     |                |                  |

| GENERAL CHARACTERISTICS    |              |
|----------------------------|--------------|
| Operating Temperature (°F) | -40°F ~ 122° |
| Storage Temperature (°F)   | -40°F ~ 140° |
| IP Rating                  | IP65         |
| IK Rating                  | -            |
| Rated Life (Hrs)           | 50,000       |
| Warranty (Yrs)             | 5            |

| ACCESSORIES |            |             |
|-------------|------------|-------------|
| Item #      | Stock Code | Description |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |

| PRODUCT DIMENSIONS   |              |  |
|----------------------|--------------|--|
| Width- in / (mm)     | 3.05" / 77.5 |  |
| Height- in / (mm)    | 10" / 254    |  |
| Depth- in / (mm)     | 10" / 254    |  |
| IK Rating            | -            |  |
| Weight (lbs)         | 4.6          |  |
| Mounting Height (ft) | -            |  |
| Cable Length (ft)    | -            |  |

| CERTIFICATIONS     |              |      |   |
|--------------------|--------------|------|---|
| UL/ETL             | ETL / cETL   | CEC  | ✓ |
| NSF/ETL Sanitation |              | JA8  |   |
| Energy Star        |              | FCC  | ✓ |
| DLC                | 5.1 Standard | RoHs | ✓ |

| DOCUMENTS |   |             |   |
|-----------|---|-------------|---|
| LM79      | ✓ | IES File    | ✓ |
| LM80      | ✓ | Dimmer List |   |
|           |   |             |   |
|           |   |             |   |

| COMMENTS |
|----------|
|          |