

|             |     |      |         |
|-------------|-----|------|---------|
| Version     | 2.0 | Date | 8/21/19 |
| Prepared By | JC  |      |         |

| PRODUCT SPECIFICATION |                            |
|-----------------------|----------------------------|
| Category              | Slim Area Light            |
| Item Number           | 7702                       |
| Stock Code            | LED-FXSAL150/30K/WH/3S     |
| Mounting              | EA6/SB/SF/WM/PM/Yoke Mount |
| Housing Color         | White                      |



| ELECTRICAL CHARACTERISTICS |          |                         |         |
|----------------------------|----------|-------------------------|---------|
| Rated Wattage (W)          | 150      | Replacement Wattage (W) | 400-575 |
| Tested Wattage (W)         | 152.3    |                         |         |
| Input Voltage (V)          | 120-277V | Surge Protect Level     | 10KV    |
| Voltage Frequency (Hz)     | 50/60    | Dimmable                | 1-10V   |
| Input Current (A)          | 1.3      | AUX (12V) Line          | -       |
| Power Factor               | >0.9     |                         |         |
| THD                        | <20%     |                         |         |

| PHOTOMETRIC CHARACTERISTICS |        |                |        |
|-----------------------------|--------|----------------|--------|
| Lumen (lm)                  | 20,604 | CCT (K)        | 3000K  |
| Efficacy (lm/w)             | 135    | Beam Angle (°) | Type 3 |
| CRI                         | >70    |                |        |

| GENERAL CHARACTERISTICS    |               |
|----------------------------|---------------|
| Operating Temperature (°F) | -40°F ~ 122°  |
| Storage Temperature (°F)   | -40°F ~ 140°F |
| IP Rating                  | IP65          |
| IK Rating                  | -             |
| Rated Life (Hrs)           | 50,000        |
| Warranty (Yrs)             | 5             |

| ACCESSORIES |             |             |
|-------------|-------------|-------------|
| Item #      | Stock Code  | Description |
| K141030     | REC3PLK/PHO | Photocell   |
|             |             |             |
|             |             |             |
|             |             |             |

| PRODUCT DIMENSIONS   |            |  |
|----------------------|------------|--|
| Width- in / (mm)     | 14.96" 380 |  |
| Height- in / (mm)    | 3.00" 76.2 |  |
| Depth- in / (mm)     | 21.57" 548 |  |
| EPA (ft²)            | -          |  |
| Weight (lbs)         | 22         |  |
| Mounting Height (ft) | -          |  |
| Cable Length (ft)    | 1.97       |  |

| CERTIFICATIONS     |     |      |   |
|--------------------|-----|------|---|
| UL/ETL             | ETL | CEC  |   |
| NSF/ETL Sanitation |     | JA8  |   |
| Energy Star        |     | FCC  | ✓ |
| DLC                |     | RoHs | ✓ |

| DOCUMENTS |   |             |   |
|-----------|---|-------------|---|
| LM79      | ✓ | IES File    | ✓ |
| LM80      | ✓ | Dimmer List |   |
|           |   |             |   |
|           |   |             |   |

| COMMENTS |
|----------|
|          |