

Version	2.0	Date	12/31/2021
Prepared By	J.C		

**PRODUCT SPECIFICATION**

Category	Commercial Strip Light
Item Number	9251
Stock Code	FXCSL44SW/48FR/8CCT3/347
Mounting	Surface Mount
Housing Color	White + Frosted Lens



**ELECTRICAL CHARACTERISTICS**

Rated Wattage (W)	44 / 36 / 28 / 22	Replacement Wattage (W)	2 x 32W T8
Tested Wattage (W)	44		
Input Voltage (V)	120 ~ 347	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.4 (max)	AUX (12V) Line	Yes
Power Factor	≥ 0.9		
THD	≤ 20%		

**PHOTOMETRIC CHARACTERISTICS**

Lumen (lm)	5720 / 4680 / 3640 / 2860	CCT (K)	3500 / 4000 / 5000
Efficacy (lm/w)	130	Beam Angle (°)	110
CRI	> 80		

**GENERAL CHARACTERISTICS**

Operating Temperature (°F)	-13 ~ 104
Storage Temperature (°F)	-13 ~ 176
IP Rating	IP20
Rated Life	50000 hrs.
Warranty	5 years

**ACCESSORIES**

Item #	Stock Code	Description
P10438	SEN-HB001VCR-1	Motion Sensor 0-10V internal 12V
7336	BAEM4-60BC/MV-A	120V ~ 277V 4W EM Driver

**PRODUCT DIMENSIONS**

Width- in (mm)	2.58 (65.5mm)	
Height- in (mm)	2.71 (68.8mm)	
Depth- in (mm)	46.6 (1183.6mm)	
EPA (ft²)	N/A	
Weight (lbs)	4.68	
Mounting Height (ft)	10 ~ 25	
Cable Length (ft)		

**CERTIFICATIONS**

UL/ETL	UL	CEC	
NSF/ETL Sanitation		JAB	
Energy Star		FCC	✓
DLC	V5.1 S	RoHs	✓

**DOCUMENTS**

LM79	✓	IES File	✓
LM80	✓	Dimmer List	

**COMMENTS**

--