


Version	2.0	Date	12/31/2021
Prepared By	J.C		

PRODUCT SPECIFICATION

Category	Commercial Strip Light
Item Number	9252
Stock Code	FXCSL68SW/96FR/8CCT3/347
Mounting	Surface Mount
Housing Color	White + Frosted Lens



ELECTRICAL CHARACTERISTICS

Rated Wattage (W)	68 / 58 / 44	Replacement Wattage (W)	2 x 59W T8
Tested Wattage (W)	68		
Input Voltage (V)	120 ~ 347	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.62 (max)	AUX (12V) Line	Yes
Power Factor	≥ 0.9		
THD	≤ 20%		

PHOTOMETRIC CHARACTERISTICS

Lumen (lm)	8840 / 7540 / 5720	CCT (K)	3500 / 4000 / 5000
Efficacy (lm/w)	130	Beam Angle (°)	110
CRI	> 80		

GENERAL CHARACTERISTICS


Operating Temperature (°F)	-13 ~ 104
Storage Temperature (°F)	-13 ~ 176
IP Rating	IP20
Rated Life	50000 hrs.
Warranty	5 years

ACCESSORIES

Item #	Stock Code	Description
P10438	SEN-HB001VCR-1	Motion Sensor 0-10V internal 12V
7334	BAEM15-48BC/MV-A	120V ~ 277V 15W EM Driver

PRODUCT DIMENSIONS

Width- in (mm)	2.58" (65.5mm)
Height- in (mm)	2.71" (68.8mm)
Depth- in (mm)	92.82" (2357.6mm)
EPA (ft²)	N/A
Weight (lbs)	9.92
Mounting Height (ft)	10 ~ 25
Cable Length (ft)	



CERTIFICATIONS

UL/ETL	UL	CEC	
NSF/ETL Sanitation		JAB	
Energy Star		FCC	✓
DLC	V5.1 S	RoHs	✓

DOCUMENTS

LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS

--