

Version	2.0	Date	12/20/19
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Post Top
Item Number	9300
Stock Code	LED-FX16PST73/850/BK
Mounting	Pole
Housing Color	Black



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	74	Replacement Wattage (W)	250
Tested Wattage (W)	74.9		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	-	AUX (12V) Line	-
Power Factor	>0.9		
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	9,361	CCT (K)	5000K
Efficacy (lm/w)	127	Beam Angle (°)	110°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 140°F
Storage Temperature (°F)	-40°F ~ 140°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7334	BAEM15-48BC/MV-A	15W Emergency Driver
K141030	REC3PLK/PHO	Photocell + 3 Prong Receptacle Kit
P10234	SEN-MC605V-D	Motion Sensor 120-277V

PRODUCT DIMENSIONS		
Width- in / (mm)	15.75" / 400	
Height- in / (mm)	22.40" / 569	
Depth- in / (mm)	2.375" / 60	
EPA (ft²)	-	
Weight (lbs)	17.86	
Mounting	Fits 2-3/8" Tenon	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS