

Version	2.0	Date	8/11/22
Prepared By	JC		

PRODUCT SPECIFICATION	
Category	Slim Wall Pack
Item Number	9311
Stock Code	LED-FXSWP45/840/BK
Mounting	Wall Mount
Housing Color	Black



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	45	Replacement Wattage (W)	250
Tested Wattage (W)	45.52		
Input Voltage (V)	120-277V	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60		
Input Current (A)	0.47	Dimmable	1-10V
Power Factor	>0.9	AUX (12V) Line	-
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	5,539	CCT (K)	4000K
Efficacy (lm/w)	122	Beam Angle (°)	140°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-22°F ~ 122°F
Storage Temperature (°F)	-40°F ~ 158°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10036	SEN-PHO-BT-MT/MV	Photocell Sensor
P10006	MT-KNC-SWP/BK	3/4" NPT Knuckle Mount for SWP- Black
P10007	MT-SF-SWP/BK	Slip Fitter Mount for SWP - Black
P10005	MT-SB-SWP/BK	Swivel Bracket for SWP - Black

PRODUCT DIMENSIONS		
Width- in / (mm)	6.6" / 167	
Height- in / (mm)	7.87" / 200	
Depth- in / (mm)	4" / 103	
EPA (ft²)	-	
Weight (lbs)	5.45	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS