

	Prod	uct Spec	
Category	LED Slim Canopy		and the latest and th
Item Code	9435		
Stock Code	FX10SCM42/850/BK-SEN	PICTURE	
Mounting	Ceiling		
Housing Color	Black		

Electric Cl	naracteristics	Photometric (Characteristics	
Rated Wattage (W)	42	Lumen (lm)	5516	
Tested Wattage (W)	41.42	Efficacy (lm/w)	133	
nput Voltage (V)	100~277	CRI	80	
Voltage Frequency (Hz)	50/60	сст (к)	5000	
nput Current (A)	0.42	Beam Angle (°)	160	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)	175	Operating Temperature	- 40°F~122°F	
Surge protect level	4KV	Storage Temperature	-40°F~140°F	
Dimmable	0-10V	IP rating	IP65	
ГНД	<20%	Rated Life	50000 hrs	
		Warranty	5 years	
•		· ·		
Product	Dimensions	Suggested	Suggested Accessory	
Weight (lbs.)	5.1	Comes with Mic	crowave Sensor	
Height (in)	3.5			
Length (in)	9.48			
Width (in)	9.48			
Mounting Height (ft)				
Mounting Height (ft) Cable Length (ft)				
	Qual	lifications		
Cable Length (ft)	Qual ETL/cETL	lifications LM79	٧	
Cable Length (ft) UL/ETL			√ √	
Cable Length (ft) UL/ETL Energy Star		LM79		
Cable Length (ft) UL/ETL Energy Star DLC	ETL/cETL	LM79 LM80	٧	
Cable Length (ft) UL/ETL Energy Star DLC CEC	ETL/cETL	LM79 LM80 IES File	٧	
	ETL/cETL	LM79 LM80 IES File FDA	٧	

Version 1.2, 9/8/2020